W. Badgett
Run Control &
Run Configuration
01/16/2002

How to start, configure and operate CDF Run Control

Run Control, main window

W. Badgett
Run Control &
Run Configuration
01/16/2002



Main Run Control Window: Includes RC State Manager, Configuration pull-down menus, Run Control Status, and Accelerator Status panels

Start Run Control:

setup fer

rc

(ace uses *cdfdaq* account)

Just 3 steps to run!

1. *Select State Manager*
2. *Select Partition*
3. *Select Configuration*

Run!

State Manager Selection

W. Badgett
Run Control &
Run Configuration
01/16/2002



Select State Manager:

- Usually **DAQ**
- GenericCalibration for calibrations unless specific menu item for given run type: e.g., QIE Calibration

Source, TDC testing are primarily for experts

The State Manager determines the flow of control when cycling through runs

Select Partition

W. Badgett
Run Control &
Run Configuration
01/16/2002

Step 2



Select partition

Select or view resources manually

Each Run Control Session must be allocate a *Partition*

Each front end crate belongs to no more than one *Partition*

Partitions prevent collisions between sessions

Partition Selector

W. Badgett
Run Control &
Run Configuration
01/16/2002

Step 2a



Select Partition:

- Cyan is free
- Yellow is owned by another
- Green is yours
- Mouse over to display owner and hardware/software status

- 0–7 are hardware partitions
- 8–15 are software partitions

Resource Selector

W. Badgett
Run Control &
Run Configuration
01/16/2002



Select Resources:

- Cyan is entirely free
- Red is entirely owned by another partition
- Blue is partially owned by another partition
- Yellow is partially yours
- Green is entirely yours
- Mouse over to display owner

Click to book/unbook
Right-click for more info

Selecting Run Configuration

W. Badgett
Run Control &
Run Configuration
01/16/2002

Step 3



Select predefined run configuration

Edit or view run configuration

Frank sez:
“This is the ace’s most important duty!”

After selecting a configuration, you’re ready to start a run!

Reset or stop luminosity counters at beginning and end of shot

Run Configuration Selector

W. Badgett
Run Control &
Run Configuration
01/16/2002



Select from predefined run configurations

- *Ace* directory contains all physics and test runs for the Ace, and is maintained by Ops Managers
- *Cosmic* directory for Cosmic Ray runs
- *Calib* directory contains calibration configurations, and is maintained by component experts in subdirectories
- Other directories for private testing purposes

Or create your own configuration!

Run Settings Window, standard

W. Badgett
Run Control &
Run Configuration
01/16/2002



Aces should know all options on this window

Global DAQ RunType

Trigger Table, coupled

CalorCalibSet, when Plug source, LED, Xenon run types

SVX Set, when SVX is used Usually FIBTEST

Consumer Selection (calibration run types only for now)

Front end crate selection Move to left to include

Run Settings, Expert Options

W. Badgett
Run Control &
Run Configuration
01/16/2002



Expert options can be enabled from the File pull-down menu

Many expert options are triggered by the selection of other options or the addition of crates

You may be asked to take special runs, e.g. MyronMode with L1Early, which are only available in the expert options

Trigger Inhibits

W. Badgett
Run Control &
Run Configuration
01/16/2002



Inhibits normally used only during physics (colliding beam) runs, otherwise set Ignore Inhibit to true

Inhibit sources are tied to the crates and components you have chosen, and are selected automatically

In an emergency, you may have to disable misbehaving inhibit signals

Inhibits cause data taking to stop, watch event rates and Inhibit LEDS

Trigger Inhibit Disable Masking

W. Badgett
Run Control &
Run Configuration
01/16/2002



Select which components should be ***disabled*** from providing an inhibit signal

Greyed options are not yet working and do not contribute to inhibits

Jonatron sez:
"Inhibitions are the Ace's most important duty!"

Data Type Selection

W. Badgett
Run Control &
Run Configuration
01/16/2002



Pull-down menu in Run Settings window selects data types

Select *Beam Data* only when colliding beams are in the Tevatron

Use DAQ Testing when just exercising the system

Tony sez:
"Selecting the Data Type is the Ace's most important Duty"

Trigger Type Selection

W. Badgett
Run Control &
Run Configuration
01/16/2002



Select *coupled* Trigger Table here for normal physics running

Select decoupled tables here for testing purposes

Coupled tables are fully specified from Level 1, Level 2 through Level 3

Synonyms:
Trigger Type =
Trigger Table =
Physics Table

Decoupled Trigger Tables

W. Badgett
Run Control &
Run Configuration
01/16/2002

Trigger Type Selector

Select a single row of parameters from the list of choices below

PHYSICSTABLE	TAG	L3	DESCRIPTION	CREATED
Physics_D_0_00	5	163	Test_L3_Filters_1stream v3 with CES patch	2001.06.29
Physics_D_0_00	5	150	Test_L3_Filters_1stream single stream all reco	2001.06.29
Physics_D_0_00	5	143	Null 2, null exe does nothing	2001.06.29
Physics_D_0_00	4	163	Test_L3_Filters_1stream v3 with CES patch	2001.06.29
Physics_D_0_00	4	150	Test_L3_Filters_1stream single stream all reco	2001.06.29
Physics_D_0_00	4	143	Null 2, null exe does nothing	2001.06.29
Physics_D_0_00	3	163	Test_L3_Filters_1stream v3 with CES patch	2001.06.29
Physics_D_0_00	3	150	Test_L3_Filters_1stream single stream all reco	2001.06.29
Physics_D_0_00	3	143	Null 2, null exe does nothing	2001.06.29
Physics_D_0_00	2	163	Test_L3_Filters_1stream v3 with CES patch	2001.06.28
Physics_D_0_00	2	150	Test_L3_Filters_1stream single stream all reco	2001.06.28
Physics_D_0_00	2	143	Null 2, null exe does nothing	2001.06.28
RATETEST	1	163	Test_L3_Filters_1stream v3 with CES patch	2001.06.26

Select | None | Cancel

Lots of *decoupled* trigger table options,due to combinatorics of unspecified Level 3 paths

None is a valid option when using the calibration trigger

Kirsten sez:
"Level 3 Rules!"

Coupled Trigger Tables

W. Badgett
Run Control &
Run Configuration
01/16/2002

Trigger Type Selector

Select a single row of parameters from the list of choices below

PHYSICSTABLE	TAG	L3	DESCRIPTION	CREATED
36x36_1_Coupled	22	153	36x36_1_Coupled v22	2001.06.27
36x36_1_Coupled	17	151	36x36_1_Coupled v17/use in case of High Luminosit...	2001.06.22
36x36_1_Coupled	16	146	36x36_1_Coupled v16, no muoStub no EmClust, new...	2001.06.20
36x36_1_Coupled_noInclusive	4	152	36x36_1_Coupled_noInclusive v3/use in case of High...	2001.06.22
36x36_1_Coupled_noInclusive	2	147	36x36_1_Coupled_noInclusive v2, no muoStub no Em...	2001.06.20
Physics_0_00	2	161	Physics_0_00 v2 with CES patch	2001.07.07
Physics_0_00	2	156	Physics_0_00 2	2001.06.29
Physics_0_00_00	6	155	Physics_0_00_00 v6	2001.06.29
Physics_0_00_00	5	154	Physics_0_00_00 v5	2001.06.27
Physics_I_0_00	1	162	Physics_I_0_00 v1 with CES patch	2001.07.07
Physics_I_0_00	1	157	Physics_I_0_00 1: With inclusive stream	2001.06.29

Select | None | Cancel

Coupled Trigger Tables are used for real physics (colliding beams) running

Your Ops Manager will tell you which one to use and which are for special test runs

Greg Sez: “Selecting the correct Trigger Table is the Ace’s most important duty!” (plus bringing Greg doughnut)

Crate Editor

W. Badgett
Run Control &
Run Configuration
01/16/2002



CrateEditor shows which cards will be read out, grouped by bank

Cards can be removed from readout, but only in **emergencies**
Notify expert *immediately* if you remove a card!

Component expert? Select card and press *Edit* for more info on the card
Use caution when changed database connection

Proxy Control Menu

W. Badgett
Run Control &
Run Configuration
01/16/2002



The Proxy gives you control over remote data acquisition processes:

- Software Event Builder
- Database Broker (not yet)
- Consumer Monitor
- Calibration Consumers
- Resource Manager
- Physics Consumers (to be implemented)

SoftEvb Proxy Viewer

W. Badgett
Run Control &
Run Configuration
01/16/2002

If you don't get responses from the Software Event Builder during transitions, then check the SoftEvb Proxy, and stop and/or restart if needed

Status colors:

- Green: Up and running
- Cyan: not running

Click on main button for detailed information

CalibConsumer Proxy

W. Badgett
Run Control &
Run Configuration
01/16/2002

Use the Calibration Consumer Proxy to see if your calibration consumer is still running

Resource Manager Proxy

W. Badgett
Run Control &
Run Configuration
01/16/2002



Having a problem with *Sticky Partitions*?
Try restarting the ResMgr_Prd
You can't hurt anything!

Transition Sequencing

W. Badgett
Run Control &
Run Configuration
01/16/2002



At *Start* state, select all desired clients and *Partition*

At *Idle* state, configuration must be fixed, then *ColdStart*

At *Ready* state, *Activate*

When *Active* and ready to finish run, *End*
To fix timeouts, try *Halt Recover Run*

Abort and *Reset* always available to get you out of sticky situations
Use sparingly!

Transitions

- **Partition**: Select front end crates and clients for the run; configure trigger and return crosspoints
- **WarmStart**/**ColdStart**: Configure crates and clients with info that could change run by run (slow)
  - **ColdStart**: Full download (when in doubt, ColdStart)
  - **WarmStart**: Selected clients do limited download when no changes
- **Activate**: Final step to enable system to take data (fast)
- **End**: Normal end of run, produces end of run summaries
- **Abort**: Return to Idle when no other option available
- **Pause**: Briefly stop data taking (HV trips, flying wires, inhibits)
- **Halt**/**Recover**/**Run**: Fast system error recovery

Calibration State Managers

W. Badgett
Run Control &
Run Configuration
01/16/2002



QIE Calibration State Manager

Calibrating: Transitory state, will drop to Done when all front end crates are complete

Know where Calibration Consumer log files are kept: ~cdfdaq/consumers/log

CalibLoad special option to do full download of AdMem FRAMs, by expert request only

Calibration may be done in software, no hardware triggers are generated

Sample Transition Errors

W. Badgett
Run Control &
Run Configuration
01/16/2002



During your Run Control session, you will sometimes see warning messages pop up
This example tells you are missing some important crates during a beam physics run

Do **NOT** ignore any of these messages!

If you do not understand a message, contact the appropriate expert immediately

Reply & Acknowledgments Window

W. Badgett
Run Control &
Run Configuration
01/16/2002



Window should always be visible

Words too small to read? Stretch the window!

This window indicates the transition status of clients:

- Butter yellow: RC has not sent transition
- Margarine yellow: RC has send transition, waiting for acknowledgment
- Green Client sent successful acknowledgment
- Red Client sent error

Click on the client button for more info and the client's *Local Controller*

Local Client Controller

W. Badgett
Run Control &
Run Configuration
01/16/2002



File menu gives you access to the contents of the configuration messages sent to the client

Allows you to shepherd individual clients through the transitions
Can be used if one client out of many fail a transition
Be careful to retain the same configuration!!

Avi sez: “We need a mouse click database!”

VmeBusScan Button

W. Badgett
Run Control &
Run Configuration
01/16/2002

b0cot03 VmeBusScan

File

```
VmeBusScan message
  PartitionId:        7
  IpAddress:          131.225.237.63
  Ethernet:           08:00:3e:27:c0:91
  Slot: 2  Id:  0133 001 TRACER__V2.1A
  Slot: 7  Id:  0575 009 MICHIGAN TDC LVDS Rev D
  Slot: 8  Id:  0556 009 MICHIGAN TDC LVDS Rev D
  Slot: 9  Id:  0555 009 MICHIGAN TDC LVDS Rev D
  Slot: 10  Id:  0514 009 MICHIGAN TDC LVDS Rev D
  Slot: 11  Id:  0704 009 MICHIGAN TDC LVDS Rev D
  Slot: 12  Id:  0588 009 MICHIGAN TDC LVDS Rev D
  Slot: 13  Id:  0525 009 MICHIGAN TDC LVDS Rev D
  Slot: 14  Id:  0596 009 MICHIGAN TDC LVDS Rev D
  Slot: 15  Id:  0595 009 MICHIGAN TDC LVDS Rev D
  Slot: 16  Id:  0682 009 MICHIGAN TDC LVDS Rev D
  Slot: 17  Id:  0635 009 MICHIGAN TDC LVDS Rev D
  Slot: 18  Id:  0714 009 MICHIGAN TDC LVDS Rev D
  Slot: 19  Id:  0522 009 MICHIGAN TDC LVDS Rev D
  Slot: 20  Id:  0589 009 MICHIGAN TDC LVDS Rev D
  Slot: 21  Id:  0655 009 MICHIGAN TDC LVDS Rev D
```

Choosing <u>VmeBusScan</u> from the Local Controller window returns a scan of all cards in the front end crate

Useful for verifying the presence and basic functionality of readout cards

End of Run Status Box

W. Badgett
Run Control &
Run Configuration
01/16/2002



At the end of a run you will be presented with a comment box: enter any pertinent run informations

At the end of a beam physics run, you must also decide the basic run quality. When in doubt, choose *Potentially Good*
Determines whether run is <u>processed offline!</u>

DaqMon

W. Badgett
Run Control &
Run Configuration
01/16/2002



Watching Run Control status is your first line of defense
Plus, many monitoring tools are available

DaqMon is your gateway to many monitors:

setup fer

daqmon

And provides a quick glimpse status of all systems

VxMon

W. Badgett
Run Control &
Run Configuration
01/16/2002



At-a-glance summary of all front end crates in the system

Arnd sez: “Monitoring the Front End crates is the Ace’s most important job”

ScalerMonitor

W. Badgett
Run Control &
Run Configuration
01/16/2002



Scaler Monitor gives very important information about the trigger rates

Watch trigger rates and deadtimes for a happy data acquisition system

Deadtime should be low
Trigger rates should be non-zero, but not high enough to saturate the DAQ

Conclusion

- DAQ Ace's main responsibility is operation of Run Control
- Before your shift, come to CDF control room and try out Run Control features, learn from experienced Aces and other DAQ experts
- Don't understand a feature or warning? Don't ignore! Find out! Page experts if necessary!